

REMOTE AIR COOLED CONDENSER - SCREW - 407C														
Model	THR (Btu/Hr)	AIR COOLED CONDENSER { T _{amb} = 95 F T _{cond} = 120 F }												
		Use for Chiller Model	Refriger. Circuits	Fans 1140 RPM Motors, 1 ½ HP			Connection Size OD (inch)		Refrigerant Charge (lbs)		Dimensions (inch)			Shipping Weight (lbs)
				Wide/Long	Row	Fins/Inch	Inlet	Outlet	Summer	Winter	L	W	H	
SINGLE SCREW COMPRESSOR - CONDENSERLESS AIR COOLED CHILLERS														
TRAC-060SSW	758,000	WCL060SSW	1	1 X 4	4	0 9	2 1/8	1 5/8	34	140	219	52	49	1,630
TRAC-070SSW	895,000	WCL070SSW	1	1 X 5	3	1 2	2 1/8	2 1/8	32	130	273	52	53	2,170
TRAC-080SSW	1,029,000	WCL080SSW	1	1 X 5	4	1 2	2 1/8	2 1/8	43	174	273	52	53	2,335
TRAC-090SSW	1,171,000	WCL090SSW	1	1 X 6	4	1 2	2 1/8	1 5/8	95	388	327	52	53	3,000
TRAC-100SSW	1,456,000	WCL100SSW	1	2 X 4	3	1 2	(2) 2 1/8	(2) 1 5/8	52	209	219	97	49	2,835
TRAC-120SSW	1,659,000	WCL120SSW	1	2 X 4	4	1 2	(2) 2 1/8	(2) 1 5/8	69	279	219	97	49	3,100
TRAC-140SSW	1,896,000	WCL140SSW	1	2 X 5	4	0 9	2 1/8	2 1/8	86	348	273	97	53	4,200

ALL MODELS COME WITH FAN CYCLING FROM THE 2nd FAN ON.

OPTIONS AVAILABLE:

- 1 – COPPER FINES
- 2 – COATED FINES
- 3 – FAN SPEED CONTROL OF FIRST FAN
- 4 – 830 RPM LOW NOISE FANS