

REMOTE AIR COOLED CONDENSER - SCROLL – 407C														
Model	THR (Btu/Hr)	AIR COOLED CONDENSER { T _{amb} = 95 F T _{cond} = 120 F }												
		Use for Chiller Model	Refriger. Circuits	Fans 1140 RPM Motors, 1 ½ HP			Connection Size OD (inch)		Refrigerant Charge (lbs)		Dimensions (inch)			Shipping Weight (lbs)
				Wide/Long	Row	Fins/Inch	Inlet	Outlet	Summer	Winter	L	W	H	
DUAL SCROLL COMPRESSOR - CONDENSERLESS AIR COOLED CHILLERS														
TRAC-10DZW	146,000	WCL010DZW	2	1 X 1	3	0 9	1 3/8	1 1/8	7	28	57	52	49	490
TRAC-15DZW	227,000	WCL015DZW	2	1 X 2	2	0 9	1 5/8	1 3/8	9	36	111	52	49	755
TRAC-20DZW	301,000	WCL020DZW	2	1 X 2	3	0 9	1 5/8	1 3/8	13	53	111	52	49	815
TRAC-25DZW	373,000	WCL025DZW	2	1 X 2	4	0 9	1 5/8	1 3/8	17	71	111	52	49	870
TRAC-30DZW	441,000	WCL030DZW	2	1 X 3	3	0 9	2 1/8	1 5/8	19	79	165	97	49	1,095
TRAC-40DZW	582,000	WCL040DZW	2	1 X 3	4	0 9	2 1/8	1 5/8	18	105	165	97	49	1,270
TRAC-50DZW	705,000	WCL050DZW	2	2 X 2	3	1 2	(2) 1 5/8	(2) 1 3/8	26	107	111	97	49	1,535
TRAC-70DZW	906,000	WCL070DZW	2	2 X 3	3	0 9	(2) 2 1/8	(2) 1 5/8	39	158	165	97	49	2,145

ALL MODELS COME WITH FAN CYCLING FROM THE 2nd FAN ON.

OPTIONS AVAILABLE:

- 1 – COPPERS FINS
- 2 – COATED FINS
- 3 – FAN SPEED CONTROL OF FIRST FAN
- 4 – 830 RPM LOW NOISE FANS